


FETDETERRA

	Product	Tapialblock® 40/100/15
	Dimensions	40 x 100 x 15 cm
	Weight	125 kg
	Wall thickness	40 cm

Appearance and surface	Rugged surface texture, with sporadic appearance of coarse aggregate as finishing texture
Finished	Sighted surface
Placement	Exterior and interior
Colour	Earth
Area	6,7 blocks/m2.

Density	2.000 Kg/m3
Compression resistance	5,0 N/mm ²
Cycle resistance moistening / drying	Suitable
Resistance to erosion	Suitable
Water absorption test by capillarity	4,5 %
Oxidable organic material content	0,06 %
Impact resistance	> 24,6 Joules
Fire resistance	A1
Coefficient of thermal conductivity	0,778 W/m·K
Specific heat	2,05 MJ/m3K
Thermal resistance	0,514 m2·K/W
Thermal inertia - thermal damping	83,74%
Thermal inertia - thermal gap	9,15 hours
Reduction index. R _A	66 dBA

The blocks are presented in indivisible pallets.

It should be stored in a protected and dry place. Do not stack pallets.

blocks/pallet	Quantity/pallet	weight/pallet	Dimensions/pallet
9 blocks / pallet	1,34 m2/pallet	1.125 kg/pallet	120 x 120 cm



DATA SHEET